

# ***Regenerative Stormwater Conveyance:***


---

Monitoring and Analysis in the Piedmont  
Region of North Carolina

*Simon Gregg, EI, LEED Green Associate  
Sarah Waickowski, EI  
William F. Hunt, III, PE, PhD, DWRE  
Dept. of Biological and Agricultural Engineering  
North Carolina State University*

# Background

- + innovative technique to convey and treat stormwater
- + sequence of grade control structures and pools
  - + riffles, boulder-weirs, cascade
- + 80% sand 20% wood chip media to raise the stream bed
- + used to stabilize eroded gullies
- + promote infiltration & improve hyporheic interactions
- + guidance from Anne Arundel County, MD



# Background

---

## TREATMENT MECHANISMS

- + velocity reduction & settling
  - + Stoke's Law
- + media filtration & adsorption to organic matter
  - + Darcy's Law
  - + Cation Exchange Capacity
- + denitrification
- + biological uptake



figure 4. Clements Creek, MD pre-construction  
source: ecosystemrestoration.com




figure 5. Carriage Hills RSC Clements Creek, MD  
source: ecosystemrestoration.com




# Site Location


## Municipalities



## Ecoregions



## Drainage Basins



## Wake County







figure 6. Morrisville, NC RSC location

# Site Description



# Site Description

## DRAINAGE AREAS

Dry Pond

Secondary Inlet

**7.2** ha


**12.4** ha

Run-On

**0.7** ha

COMPOSITE CN

**85**



# Design Characteristics

- + total storage volume:  $3.17\text{-m}^3$
- + 25-mm runoff volume:  $876.07\text{-m}^3$
- + % sized 0.4%
- + Loading ratio: 25,000:1

figure 10. Morrisville RSC profile  
source: Stantec Construction Doc.




figure 11. Morrisville RSC

# Monitoring Design

## EQUIPMENT

- + ISCO 6712 automated samplers
- + HOBO U20 water level loggers
- + HOBO manual & tipping bucket rain gauge
- + compound weirs w/ end contractions
- + interevent baseflow grab samples



figure 12. monitoring methods



# Preliminary Results

**83%**  
VOLUME  
REDUCTION

**192%**  
PEAK FLOW  
INCREASE






figure 13. Morrisville RSC event water balance

# Previous Research

- + 4 peer-reviewed articles
  - + 5 reports of RSC performance
- + piedmont & coastal plains
- + drainage areas: 0.3 - 94-ha
- + loading ratios: 24 - 310:1
- + slopes: 0.8 - 12.5%
- + storage ratio: 0.42 - 3.34:1
  - +  $SR = V_{\text{surface}} / V_{\text{media}}$
- + inconsistency in methods, reporting, & analysis



# Previous Research

---

- + potential for media clogging
- + media saturation limits available storage
- + trend of under sizing

## DURHAM RSC

**+10%**  
VOLUME  
REDUCTION

**21%**  
PEAK FLOW  
REDUCTION

## DURHAM RSC

**10%**  
TSS  
REDUCTION

**4.4%**  
TN  
REDUCTION

**6.8%**  
TP  
REDUCTION

# Previous Research

---

- + high media OM can leach TAN & TKN in interevent periods
  - + denitrification vs. DNRA
- + WQ performance scattered
  - + TSS: 30-70% reduction
  - + TN: 25-50% reduction
  - + TP: 30-70% reduction

## WELL DRAINED RSCs

**>80%**  
**VOLUME**  
**REDUCTION**

**>75%**  
**PEAK FLOW**  
**REDUCTION**

## ALAMANCE RSC

**94%**  
**TSS**  
**REDUCTION**

**81%**  
**TN**  
**REDUCTION**

**84%**  
**TP**  
**REDUCTION**

# Recommendations

<b>DESIGN VOLUME</b>	+ 38-mm Coastal Plains; + 25-mm elsewhere	Koryto et al. (2017); Cizek et al. (2016); Koryto et al. (2018)
<b>LOADING RATIO</b>	+ 80 - 120:1; depends on storage demand	Koryto et al. (2017); Cizek et al. (2016); Koryto et al. (2018)
<b>STORAGE RATIO</b>	+ 0.5 - 1.5:1; lower ratios improve surface-to-seepage	Koryto et al. (2017); Cizek et al. (2016); Koryto et al. (2018); Cizek et al. (2017)
<b>SLOPE</b>	+ depends on site; steeper slopes require larger structures	Flores et al. (2012); Koryto et al. (2017); Cizek et al. (2016)
<b>IN-STREAM STRUCTURES</b>	+ larger in-stream structures improve hyporheic exchange	Hester & Doyle (2008)
<b>CONSTRUCTION TECHNIQUES</b>	+ gully or exfiltration trench; rake subsoils; pool 1 forebay; SHWT	Cizek et al. (2016); Koryto et al. (2017); Brown & Hunt (2009); Filoso (2012); Hsieh & Davis (2005a); Hunt et al. (2006)
<b>VEGETATION</b>	+ yes; zone planting	Li et al., (2009); Wardynski & Hunt, (2012)
<b>MEDIA</b>	+ 80-85% coarse sand, 10-15% OM, 0-5% fines; P-index $\leq$ 30 in NSW P-index $\leq$ 50 elsewhere	Hunt et al. (2006); Hsieh & Davis (2005a); Koryto et al. (2017); Cizek et al. (2016)

# Questions?

---



# References

---

- + Brown, R. A., & Hunt, W. F. (2009). Effects of Media Depth on Bioretention Performance in the Upper Coastal Plain of North Carolina and Bioretention Construction Impacts Study. World Environmental and Water Resources Congress.
- + Cizek, A. R., Hunt, W. F., Winston, R. J., & Lauffer, M. S. (2017). Hydrologic Performance of Regenerative Stormwater Conveyance in the North Carolina Coastal Plain. *Journal of Environmental Engineering*, 143(9).
- + Cizek, A. R., Hunt, W. F., Winston, R. J., Waickowski, S., Narayanaswamy, K., & Lauffer, M. S. (2016). Water Quality and Hydrologic Performance of a Regenerative Stormwater Conveyance (RSC) in the Piedmont of North Carolina. *Journal of Environmental Engineering*.
- + Filoso, S. (2012). Assessing the Effectiveness of Regenerative Stormwater Conveyance in reducing Sediment and Nutrient Loads to Three Mid-River Creeks in the Severn River watershed, (410), 1–22.
- + Flores, H., Mcmonigle, D., & Underwood, K. (2012). Design Guidelines for Regenerative Step Pool Storm Conveyance.
- + Hester, E. T., & Doyle, M. W. (2008). In-stream geomorphic structures as drivers of hyporheic exchange. *Water Resources Research*, 44(3).
- + Hsieh, C., & Davis, A. P. (2005a). Evaluation and Optimization of Bioretention Media for Treatment of Urban Storm Water Runoff. *Journal of Environmental Engineering*, 131, 1521–1531.
- + Hunt, W. F., Jarrett, A. R. R., Smith, J. T., & Sharkey, L. J. (2006). Evaluating Bioretention Hydrology and Nutrient Removal at Three Field Sites in North Carolina. *Journal of Irrigation and Drainage Engineering*, 132(6).
- + Koryto, K. M., Asce, M., Hunt, W. F., Arellano, C., & Page, J. L. (2018). Performance of Regenerative Stormwater Conveyance on the Removal of Dissolved Pollutants: Field Scale Simulation Study, 144(6), 1–13.
- + Koryto, K. M., Hunt, W. F., & Page, J. L. (2017). Hydrologic and water quality performance of regenerative stormwater conveyance installed to stabilize an eroded outfall. *Ecological Engineering*, 108, 263–276.
- + Li, H., Sharkey, L. J., Asce, M., Hunt, W. F., Davis, A. P., & Asce, F. (n.d.). Mitigation of Impervious Surface Hydrology Using Bioretention in North Carolina and Maryland.
- + Wardynski, B. J., & Hunt, W. F. (2012). Are Bioretention Cells Being Installed Per Design Standards in North Carolina? A Field Study. *Journal of Environmental Engineering*, 138(12), 1210–1217.