Using Stream Enhancement in Urban
Settings to Protect Valuable Infrastructure
and Prevent Potential Water Quality Impacts
From Infrastructure Failure

Presented by:
Daren Pait, PE, CFM
Jason Diaz, PE, CFM





Outline of presentation

- Overview of importance of infrastructure protection
- Review several example projects and associated costs
 - Fourmile Creek
 - Force main example
 - Long Creek Spot Fix
 - · Long Creek Restoration

Urbanization Stressors

- · Increased impervious area in watersheds
- Increasing population that needs SS services
- Increase in length of sanitary sewer pipes along stream banks and aerial crossings
- Results in an increase in locations where infrastructure needs to be protected from bank erosion





Sanitary Sewer Spills

- 19,500 sewer systems nationwide, 50 billion gallons per day of raw sewage (epa.gov)
- 23,000 75,000 sanitary sewer overflows per year
- Much of SS infrastructure is between 30 and 100 years old
- Estimates of 1 billion +/- gallons of sewage spilled annually
- "In rivers, streams, and estuaries, the major contaminants contributing to the impairment were pathogens, nutrients, and metals – all contaminants typically found in sewage" - EPA's National Water Quality Inventory Report.






Charlotte Water Example




- ♦ Over 3,000 miles of streams





Charlotte Water Assistance


- CW maintenance staff identify stability issues
- Send locations of most concern to KH to assess
- Prioritize sites based on risk of failure
- CW authorizes design and repair
- Currently designing 16 separate stabilization/infrastructure protection sites
- 8 have gone to construction over past year



Charlotte Water annual SSOs




Reach Assessment and Prioritization





Utilizing LiDAR and GIS to Locate Potential Failures







- Identified as one of 16 locations by maintenance staff
- Accelerated erosion of about
 12" lateral movement per year
- 10-year storm event contained within banks (very incised)







Fourmile Creek – Before





Fourmile Creek – Before





Fourmile Creek - Construction Costs

- First designed as boulder toe protection with rock vane, and associated stone armoring for structure.
- Construction entrance/haul road was along sanitary sewer easement
- Only access was through private asphalt road
- Stream contractor was responsible for repairs
- First bids averaged \$230,000
- Re-designed as toe-wood protection and vegetated soil lifts
- Re-bid price came in at \$78,000











Fourmile Creek – After Hurricane Matthew

















Force Main Conflict

- 24" Force Main, 80 PSI
- 1.2 square mile drainage area for stream


















Long Creek





Long Creek - Before

- What Happened
- Includes 3,100 linear feet of channel re-location
- Qualified for Clean Water
 Management Trust Fund Grant





Long Creek - Before





Long Creek - Before





Long Creek – During Construction





Recent Spill Example

- 15.4 million-gallon (47 acre-feet) raw sewage
- Hard to predict (tree fell causing erosion)
- Prevention costs 10% of fixing after a spill (not counting environmental damage)



Depiction of how creek flow washed away the soil around a sewer pipe, causing it to collapse and spill.

Image Source: Catawba Riverkeeper





Recent Spill Example





Recent Spill Example



Other Examples – Mallard Creek





















Thank You

Daren Pait, PE, CFM

<u>Daren.Pait@kimley-horn.com</u>

704.319.7699

Jason Diaz, PE, CFM

<u>Jason.Diaz@Kimley-horn.com</u>

704-954-7464

